


# PDU Technology Specification

No.	Item	Detailed Description		
1	Product Series	AUE2230		
2	Socket Type	Single IEC320 C13 Socket[6];		
3	Socket Quantity	6		
4	Power Input	Left end single input		
5	Bracket Install	Frontal installation		
6	Cable with plug	IEC320 C14 10A plug		
7	Control Function	No controlling function		
8	Protection Function	No protecting function		
9	Case	Black		
10	Cable Specification	3 x 1.0 mm <sup>2</sup> x 2M		
11	Product Size	L x W x H = 482.6 x 68 x 44.4 mm		
12	Mounting Length	465 mm		
13	Case Length	429.5 mm		
14	Fittings	2pcs $\phi$ 6×16mm cross bolt, 2pcs M6 float nut		
15	Product Label	Product Name	Designated Power Distribution Unit for Cabinet	
		Specification Model	16-8100	
		Rating voltage	250VAC 50/60Hz	
		Rating Current	10A	
		Max. Current		
		Max. Power	2500 W	
		Safety Authentication	CE	
		Logo	RoHS	
		Producer		
No.	Add-In			
1	Socket assemble	No		
2	Interior Connection Wire	1.5 mm <sup>2</sup>		
3	Interior Connection Style	Standard connection		
4	Fix the Cable	Small cable clamp		
5	Module Assemble ( form left to right )	Please see the following picture		
6	Others	No		
<b>Made by:</b>		<b>Customer confirm:</b>	<b>Check:</b>	<b>Authorize:</b>

**This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.**

# PDU Technology Specification

Preview



IEC320 C14 10A plug

**DIMENSION AND TOLERANCES**  
( Unit: mm )

Length: 482.6    Mounting length: 465  
 Width: 68    Case length: 429.5  
 Height: 44.4    case tolerance:  $\pm 1.0$

SIGN		DATE		Product name	Designated Power Distribution Unit for Cabinet
DRAWN					
CHK'D				Customer's code	
APP'D				Drawing number	
				Edition number	