

PDU Technology Specification

No.	Item	Detailed Description		
1	Product Series	AUE2230		
2	Socket Type	DIN49440 16A Socket[36];		
3	Socket Quantity	36		
4	Power Input	Left end single input		
5	Bracket Install	Inverse installation		
6	Cable with plug	IEC60309 plug (32A 3P+N+E)		
7	Control Function	No controlling function		
8	Protection Function	No protecting function		
9	Case	Black		
10	Cable Specification	5x 6.0 mm ² x 2M		
11	Product Size	L x W x H = 1726 x 68 x 44.4 mm		
12	Mounting Length	1699.5 mm		
13	Case Length	1673 mm		
14	Fittings	2pcs φ6×16mm cross bolt, 2pcs M6 float nut		
15	Product Label	Product Name	Designated Power Distribution Unit for Cabinet	
		Specification Model	16-8234	
		Rating voltage	380VAC input/ 250VAC output	
		Rating Current	3×32A	
		Max. Current		
		Max. Power		
		Safety Authentication	CE	
		Logo	RoHS	
		Producer		
No.	Add-In			
1	Socket assemble	No		
2	Interior Connection Wire	2.5 mm ²		
3	Interior Connection Style	Group connection		
4	Fix the Cable	Cable clamp		
5	Module Assemble (form left to right)	Please see the following picture		
6	Others	No		
Made by:		Customer confirm:	Check:	Authorize:

This technology specification is for: design product for customer and confirm customer's requirements, and is also the basic gist for arranging production.

PDU Technology Specification

Preview



IEC60309 plug (32A 3P+N+E)

DIMENSION AND TOLERANCES
(Unit: mm)

Length: 1726 Mounting length: 1699.5
 Width: 68 Case length: 1673
 Height: 44.4 case tolerance: ± 1.0

	SIGN	DATE	Product name
DRAWN			Designated Power Distribution Unit for Cabinet
CHK'D		Part number	
APP'D		Customer's code	
		Drawing number	
		Edition number	